

IMPULSO | GRX | YTB8C



The image shown is indicative only. Components and graphic detail may differ from actual model. Bianchi reserves the right to amend specifications and/or prices.

COLOR	AK - Fall Green / Carbon UD Fork Full Glossy IP - CK16 / Aquamarine
FRAME	IMPULSO gravel ALU 11/8 aheadset ,seat post 31.6mm, thru axle 12x142mm, flat mount disc version, PF41, compatible with 40mm tire and mudguard and rear carrier predisposition. sizes 47-50-53-55-57-59-61-63cm
SEATPOST CLAMP	Aluminium clamp, light weight, 35mm anti-crimp
HEADSET	Fsa NO.8B/ZS4D 1-1/8
FORK	Full Carbon 11/8, flat mount, disc brake, thru axle 12x100mm
SHIFTER	Shimano GRX Hydraulic disc brake
REAR DERAILLEUR	Shimano GRX
FRONT DERAILLEUR	Shimano GRX
CRANKSET	GRX 175mm, 48-31T w/o BB parts Crank Length: 170mm-47-54cm, 172.5mm-55-59cm, 175mm-60-63cm
BOTTOM BRACKET	Shimano, SM-BB72-41B, press fit for road
CHAIN	Shimano
CASSETTE / FREEWHEEL	Shimano 105
BRAKE	Shimano flat mount hydraulic disc brake, included in the shifter
BRAKE LEVER	included

DISC ROTOR	Shimano rotor for disc brake center lock, 160mm
FRONT HUB	Formula CL-712 road disc , alloy 32h, center lock, thru axle 12x100mm, 2SB bearing
REAR HUB	Formula road disc , center lock, thru axle 12x142mm, 4SB bearing for Shimano
RIM/WHEELSET	Velomann disc 700c 622-21, profile 24mm, sleeve join, 32hole, tubeless ready
TIRE	Kenda Alluvium 700x40, 60TPI
STEM	Velomann, Alloy 6061, raise +/- 7°, height 38mm, Oversize, 1 1/8, Ext: 70mm-47cm, 90mm-50/53cm, 100mm-55cm, 110mm-57/59cm, 120mm-61/63cm
HANDLEBAR	Velomann Aluminum 6061, reach 70mm, flare angle 16°, drop cc 120 x size 40cm and 130mm x size 42-44-46cm, size: 40cm 47/50/53 - 42cm 55/57/59 - 44cm 61/63
GRIP / TAPE	Bianchi cork, black
SEATPOST	Velomann Alloy shaft AL6061, alloy head, 15mm offset, 31,6mm, Length: 350mm-47/63cm
SADDLE	Velomann, length/wide 278x144mm